



FABRIC SPECIFICATION SHEET

Style		FM4G - Armourtex
Construction		Polyester multifilament scrim supported needlefelt
Colour		Gray
Weight	g/m ²	490 - 595
Thickness	mm	1.66 - 2.16
Air Permeability	cc/cm ² /sec @ 12.7 mm H ₂ O	3.5 - 6.1
Scrim	g/m ²	100, Multi-filament
Max. Linial Shrinkage	For 120 min @ 150 °C	3%
Fibre		Epitropic Polyester fibres
Bursting Strength	kg/cm ²	35
Tensile Strength	kg/5 cm width	MD 102 CD 133
Surface Treatment		Infra-red fibrelocked dust
Finish		Heat set and calendered
Max. Operating Temperature	°C	135
Application		Anti-static needlefelt for reverse-pulse dust collectors

FM4G

Filtercorp International Limited

22-24 Bay Park Place, P O Box 66-080
Beach Haven 0749, Auckland, New Zealand
Ph: (09)481-9999 Fax: (09)483-4355
Email: akld@filtercorp.biz

152 Hazeldean Road
Addington 8024, Christchurch, New Zealand
Ph: (03)377-9200 Fax: (03)377-9212
Email: chch@filtercorp.biz

Web site: <http://www.filtercorp.biz>