



FABRIC SPECIFICATION SHEET

| | | |
|-----------------------------------|---|------------|
| Style | MDF400G | |
| Construction | Polyester multifilament scrim supported needle-felt with carbon | |
| Colour | White | |
| Weight | g/m ² | 400 ± 20 |
| Thickness | mm | 2.14 ± 10% |
| Air Permeability | cc/cm ² /sec @ 127Pa | 5.0-7.5 |
| Max. Linial Shrinkage | For 240 min @ 170 °C | 2.99% |
| Fibre | 97% Virgin Polyester 3% Electrostatic Carbon String Lines | |
| Bursting Strength | kg/cm ² | 52+ |
| Surface Treatment | Heat set and singed one side | |
| Finish | PTFE membrane (DGF-008-400) | |
| Max. Operating Temperature | °C | 130 |
| Application | Anti-static needlefelt for static dust collectors | |

MDF400G

Filtercorp International Limited

22-24 Bay Park Place, P O Box 66-080
Beach Haven, Auckland, New Zealand
Ph: (09)483-7149 Fax: (09)483-4355
Email: akld@filtercorp.co.nz

152 Hazeldean Road
Addington, Christchurch, New Zealand
Ph: (03)377-9200 Fax: (03)377-9212
Email: chch@filtercorp.co.nz

Web site: <http://www.filtercorp.co.nz>